



- 1 COPPER ALLOY PER ASTM B301
- 2 1.27 μm [50 μin] MIN GOLD PER ASTM B488
OVER 2.54 μm [100 μin] MIN NICKEL PER
QQ-N-290 ON ENTIRE STOCK.
- 3. APPLICATION TOOLING:
CRIMPING TOOL: M22520/23-01
DIE SET: M22520/23-02
LOCATOR: TYCO P/N 1738331-1
EXTRACTION TOOL: M81969/28-01
- 4. WIRE ACCOMMODATED: 8 AWG
STRIP LENGTH: 9.60 [.378] - 10.10 [.398]
- 5. THIS PRODUCT IS SOLD BY TYCO ELECTRONICS
UNDER A LICENSE FROM RADIAL SA

PRELIMINARY
NOT RELEASED FOR
PRODUCTION

DIMENSIONS : mm [inch]

Tyco PN - 1738019-1

THIS DRAWING IS A CONTROLLED DOCUMENT.		CHK	22MAR2004	Tyco Electronics Corporation Harrisburg, Pa 17105-3608	
DIMENSIONS:		APD	---	POWER CONTACT, PIN, CRIMP TERMINATION	
mm [INCHES]		PRODUCT SPEC	---	SIZE 5	
DIMENSIONS UNLESS SPECIFIED:		APPLICATION SPEC	---	GPR	
0 P.L.C. =		SIZE	---	DATE CODE	DRAWING NO
1 P.L.C. =		WEIGHT	---	A0	00779
2 P.L.C. =		CUSTOMER DRAWING	---	SCALE	1:1
3 P.L.C. =				SHEET	1 of 1
4 P.L.C. =				REV	0
MATERIAL					